




ZŠ STAVICE STÁL ZBOŘENOMĚ, III. (485)									
#	střední [m]	dlouhý [m]	hlav. [m]	dlouhý smezna [m]	#	#	#	#	#
6	#12	4.63	84	386.92					
7	#12	0.705	16	11.28					
8	#12	1.10	16	17.60					
9	#12	3.12	84	372.48					
10	#12	1.45	16	23.2					
11	#12	0.565	16	6.92					
12	#6	2.655	74	306.65					
13	#6	2.675	120	32.0					
14	#6	2.52	52	13.04					
15	#6	0.56	26	7.16					
16	#6	1.34	26	34.64					
17	#6	1.34	26						
18	#12	1.52	4						
19	#12	2.23	4						
20	#6	0.88	22	14.56					
21	#6	0.355	33	11.66					
22	#6	0.28	44	12.32					
23	#6	0.76	13	9.88					
dlouhý (spaña [m])				46.22	863.70				775.40
spaña plošnikov (kg)				0.222	0.395				0.888
spaña celkový (kg)				10.70	315.83				688.56
					1019.09				



oparcie istniejącej płyty na ścianach szyb

wieniec W w tylnej ścianie szybu

uwaga
wymiarzy zweryfikować z danymi dostawcy dźwigu , ewentualne
rozbieżności zgłosić projektantom w celu aktualizacji wymiarowej szybu

STAL ZBROJENIOWA A-III (34GS)
BETON C 20/25 (B25)

[illegible]